

## SPECIFICATION SHEET

### CALCIUM STEARATE FG KOSHER

Characteristics	Specifications		Unit(s)
	Min.	Max.	
Identification test for calcium	To pass test		---
Identification test (freezing point or solidification point)	≥54		°C
Oxide content (as CaO)	9.0	10.5	%
Sieve residue 200 mesh		≤1.0	%
Organic volatile impurities	To pass test		---
Bulk Density		≤260	g/l
Melting Point	145	160	°C
Unsaponifiable		≤2.0	%
Loss on drying		≤4.0	%
FFA (as oleic acid)		≤1.5	%
Alkalinity (as NaOH)		≤0.1	%
Arsenic		≤3.0	ppm
Lead		≤2.0	ppm
Cadmium		≤1.0	ppm
Mercury		≤1.0	ppm
Heavy Metals (total)		≤10.0	ppm

**Quality Approved**  
**May 11, 2018**



**Daisy M. Marseille**  
**Quality Assurance Manager**

**Important:** The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal, and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Kraft Chemical assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws

